



DENT MEDIUM LED GE

This is the luminaire with a playful personality. Looking one way, and then another. Its design is enigmatic, as is the light it provides. And then there's what can be done with it, and where. Alone on a residential wall, it's minimalistic and beautiful. Together in a large public space, they become an artful lightscape with puzzling lines and angular paths.

Art. Nr. 11611032

SPECIFICATIONS

Lamp	1x LED Line 17.6W
Gear / Transfo	LED gear not incl.
Weight	0.67kg
Min. distance	0.1 m
Power supply	350mA
IP	IP20
Glow wire test	650°
Lifetime	L80 B20 @ 50.000hrs
CRI	90
CIE flux code	67/93/99/50/17
Luminaire power	17.6W
Lumen	428 Lm
Efficacy	24 Lm/W
UGR	22
Adjustability	Not Applicable
Remark	! can be installed on single and double electrical connection box

	WARM WHITE 2700K / CRI 90+	WARM WHITE 3000K / CRI 90+
black struc	11611032	11611132
white struc	11611009	11611109



DENT MEDIUM LED GE

ACCESSORIES

DRIVER-LED

13470130	CASAMBI LED GEAR 350-1050mA 25-60W
13470030	CASAMBI LED GEAR 300-1050mA 16-38W

CASAMBI

13470109	CASAMBI SWITCH WHITE
13470101	CASAMBI DIM MODULE TRE DIM
13470102	CASAMBI DIM MODULE DALI
13470100	CASAMBI DIM MODULE 1-10V

HUE-DEVICE

70000155	NIKO PURE SWITCH FOR HUE - BLACK STEEL
70000154	NIKO PURE SWITCH FOR HUE - WHITE STEEL
70000152	HUE DIMMER SWITCH
70008054	HUE SENSOR

HUE-BRIDGE

70000617	HUE BRIDGE UK
70000616	HUE BRIDGE EU

HUE-MODULE

13190130	HUE DIM CIRCUIT MODULE 150-300W 0/1-10V
----------	---

